

## ICP521630PM-01

Rechargeable Lithium Ion Polymer Battery Pack 3.7 V Safety Circuit, **IEC62133 certified** 

## **Specifications**

Renata Type ICP521630
IEC Designation ICP061732
Part Number 100691
Contact Method: Wire AWG 30

Safety Circuit Yes

Nominal Voltage 3.7 V Nominal Capacity 250 mAh Minimum Capacity 240 mAh

(0.2C cut off 3.0 V at

20°C)

Internal Impedance  $< 290 \text{ m}\Omega / 30\% \text{ SOC}$ 

Thickness (t)

Lenghth (I)

Width (w)

Max 5.7 mm

Max 31.5 mm

Max 17.0 mm

Weight

~ 5.4 q

**Charging Characteristic** 

CC/CV – Constant Current / Constant Voltage

**Dimensions** 

Voltage 4.2 V CV

Current Normal 0.5 C CC – 125 mA

Max. Charging Current 1.0 C CC – 250 mA

Temperature at Charging 0 °C .... 45 °C

**Discharge Characteristic** 

Cut off Voltage 3.0 V

Max discharge Current 2.0 C – 500 mA (for non continues discharge)

1.0 C – 250 mA (for continues discharge)

Temperature during Discharge -20 °C ... 60 °C

Cycle Life at Room Temperature > 80% of minimum capacity after 500 cycles (0.5 C

charge, 0.5 C discharge)

Storage Temperature -20 °C ... 45 °C

( 0 °C ... 30 °C recommended in case of storage for

more than 3 months)

Information and contents in this data sheet are for reference purpose only. They do not constitute any warranty or representation and are subject to change without notice. For most current information and further details, please contact your Renata representative. For safety related information please consult the ASDS document related to that product or product family. The Products of Renata SA are neither designed nor authorized for use in certain areas of application of environment. For further details we refer to our webpage <a href="https://www.renata.com/downloads/restriction\_of\_use">www.renata.com/downloads/restriction\_of\_use</a>

Rev. ICP521630 V02 08/2019

