

ICP582035PR-01

Rechargeable Lithium Ion Polymer Battery Pack 3.7 V

Safety Circuit,

Specifications

Renata Type	ICP582035
IEC Designation	ICP072137
Part Number	101029
Contact Method:	Wire AWG 30
Safety Circuit	Yes

Nominal Voltage	3.7 V
Typical Capacity	340 mAh
Minimum Capacity	330 mAh (0.2C cut off 3.0 V at 20°C)

Internal Impedance	< 350 mΩ / 30% SOC
--------------------	--------------------

Thickness (t)	Max 6.4 mm (after 500 cycles)
Length (l)	Max 37 mm (after 500 cycles)
Width (w)	Max 20.5 mm (after 500 cycles)
Weight	~ 7.3 g

Charging Characteristic

Voltage	CC/CV – Constant Current / Constant Voltage
Current Normal	4.2 V CV
Max. Charging Current	0.5 C CC – 170 mA
Temperature at Charging	1.0 C CC – 340 mA
	0 °C 45 °C

Discharge Characteristic

Cut off Voltage	3.0 V
Max discharge Current	1.0 C – 340 mA

Temperature during Discharge	-20 °C ... 60 °C
------------------------------	------------------

Cycle Life at Room Temperature	> 80% of minimum capacity after 500 cycles (0.5 C charge, 0.5 C discharge)
--------------------------------	--

Storage Temperature	-20 °C ... 45 °C (0 °C ... 30 °C recommended in case of storage for more than 3 months)
---------------------	---

Dimensions




Illustration only. For detailed drawing please contact your sales representative.

Information and contents in this data sheet are for reference purpose only. They do not constitute any warranty or representation and are subject to change without notice. For most current information and further details, please contact your Renata representative. For safety related information please consult the ASDS document related to that product or product family. The Products of Renata SA are neither designed nor authorized for use in certain areas of application of environment. For further details we refer to our webpage www.renata.com/downloads/restriction_of_use

Rev. ICP582035PR-01 V01 11/2022